



## SAFETY DATA SHEET CONCRETITE® TEXTURED

According to Regulation (EC) No 1907/2006

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	CONCRETITE® TEXTURED
PRODUCT NO.	1641
APPLICATION	For damp-proofing and decorating all types of exterior and interior masonry surfaces.
SUPPLIER	Garland Company UK Ltd, Unit 5, Glevum Works, Upton Street, Gloucester GL1 4LA UK Tel: 01452 330 646 Fax: 01452 330 657 email: info@garlandukltd.co.uk
EMERGENCY TELEPHONE	01452 330646 09:00 - 17:00 Monday to Friday

### 2 HAZARDS IDENTIFICATION

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION R52/53.

#### ENVIRONMENT

The product contains a substance which is very toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
CALCIUM CARBONATE	215-279-6	1317-65-3	10-30%	-
PERLITE		93763-70-3	1-5%	-
ZINC OXIDE	215-222-5	1314-13-2	1-5%	N;R50/53

The Full Text for all R-Phrases are Displayed in Section 16

### 4 FIRST-AID MEASURES

#### INHALATION

May cause irritation to the respiratory system. Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

#### INGESTION

May cause discomfort if swallowed. Rinse mouth thoroughly. Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Get medical attention immediately!

#### SKIN CONTACT

Prolonged skin contact may cause redness, irritation and dry skin. Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.

#### EYE CONTACT

Splashes may irritate. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 5 FIRE-FIGHTING MEASURES

**CONCRETITE® TEXTURED**

**EXTINGUISHING MEDIA**

Use fire-extinguishing media appropriate for surrounding materials.

**SPECIAL FIRE FIGHTING PROCEDURES**

Keep run-off water out of sewers and water sources. Dike for water control.

**PROTECTIVE MEASURES IN FIRE**

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

**6 ACCIDENTAL RELEASE MEASURES**

**PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

**ENVIRONMENTAL PRECAUTIONS**

Avoid discharge to the aquatic environment.

**SPILL CLEAN UP METHODS**

Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not let washing down water contaminate ponds or waterways. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

**7 HANDLING AND STORAGE**

**USAGE PRECAUTIONS**

Read and follow manufacturer's recommendations. Avoid contact with skin and eyes. Wash hands after handling.

**STORAGE PRECAUTIONS**

Store in tightly closed original container in a dry, cool and well-ventilated place. Store above freezing.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
CALCIUM CARBONATE	WEL		4 mg/m3			
PERLITE	WEL		4 mg/m3 resp.dust			
ZINC OXIDE	WEL		5 mg/m3		10 mg/m3	

WEL = Workplace Exposure Limit.

**PROTECTIVE EQUIPMENT**



**ENGINEERING MEASURES**

Provide adequate ventilation.

**HAND PROTECTION**

Use protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

**EYE PROTECTION**

Wear approved safety goggles.

**HYGIENE MEASURES**

Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke. Wash hands after handling.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

**APPEARANCE**

Liquid

**CONCRETITE® TEXTURED**

SOLUBILITY	Soluble in water.		
BOILING POINT (°C)	100°C	EVAPORATION RATE	> 1 (E/Et=1)
VOLATILE ORGANIC COMPOUND (VOC)	51 g/litre		

**10 STABILITY AND REACTIVITY**

## STABILITY

Stable under normal temperature conditions and recommended use.

**11 TOXICOLOGICAL INFORMATION**

## INHALATION

May cause irritation to the respiratory system.

## INGESTION

May cause discomfort if swallowed.

## SKIN CONTACT

Prolonged and frequent contact may cause redness and irritation.

## EYE CONTACT

May irritate eyes.

**12 ECOLOGICAL INFORMATION**

## ECOTOXICITY

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**13 DISPOSAL CONSIDERATIONS**

## DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Recover and reclaim or recycle, if practical.

**14 TRANSPORT INFORMATION**

## GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

**15 REGULATORY INFORMATION**

## RISK PHRASES

R52/53

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## SAFETY PHRASES

S60

This material and its container must be disposed of as hazardous waste.

## EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

## STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

## APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

## GUIDANCE NOTES

Workplace Exposure Limits EH40.

CONCRETITE® TEXTURED

16 OTHER INFORMATION

REVISION DATE 08-2008

RISK PHRASES IN FULL

NC Not classified.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.