



## SAFETY DATA SHEET ENERGIZER K PLUS FR

According to Regulation (EC) No 1907/2006

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	ENERGIZER K PLUS FR
PRODUCT NO.	7825
APPLICATION	For restoring and upgrading the waterproofing and fire ratings on existing smooth surfaced SBS, APP and built-up roof surfaces.
SUPPLIER	Garland Company UK Ltd, Unit 5, Glevum Works, Upton Street, Gloucester GL1 4LA UK Tel: 01452 330 646 Fax: 01452 330 657 email: info@garlandukltd.co.uk
EMERGENCY TELEPHONE	01452 330646 09:00 - 17:00 Monday to Friday

### 2 HAZARDS IDENTIFICATION

Flammable. Harmful: may cause lung damage if swallowed.

CLASSIFICATION Xn;R65. R10.

#### PHYSICAL AND CHEMICAL HAZARDS

Flammable. Vapours are heavier than air and may travel along the floor and in the bottom of containers.

#### HUMAN HEALTH

Harmful: may cause lung damage if swallowed.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
CALCIUM CARBONATE	215-279-6	1317-65-3	10-30%	-
CRYSTALLINE QUARTZ	238-878-4	14808-60-7	0.1-1%	-
MAGNESIUM CARBONATE	208-915-9	546-93-0	1-5%	-
PETROLEUM ASPHALT	232-490-9	8052-42-4	10-30%	-
PETROLEUM NAPHTHA, LIGHT AROMATIC	265-199-0	64742-95-6	10-30%	Xn;R65. R10.

The Full Text for all R-Phrases are Displayed in Section 16

### 4 FIRST-AID MEASURES

#### INHALATION

Vapours may cause drowsiness and dizziness. Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

#### INGESTION

Harmful: may cause lung damage if swallowed. Rinse mouth thoroughly. Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Get medical attention immediately!

#### SKIN CONTACT

Prolonged skin contact may cause redness, irritation and dry skin. Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.

**ENERGIZER K PLUS FR****EYE CONTACT**

Splashes may irritate. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

**5 FIRE-FIGHTING MEASURES****EXTINGUISHING MEDIA**

Extinguish with foam, carbon dioxide or dry powder. Do not use water jet as an extinguisher, as this will spread the fire.

**SPECIAL FIRE FIGHTING PROCEDURES**

Avoid breathing fire vapours. Containers close to fire should be removed immediately or cooled with water. Keep run-off water out of sewers and water sources. Dike for water control.

**UNUSUAL FIRE & EXPLOSION HAZARDS**

FLAMMABLE. Solvent vapours may form explosive mixtures with air. May travel considerable distance to source of ignition and flash back.

**SPECIFIC HAZARDS**

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Hydrocarbons.

**PROTECTIVE MEASURES IN FIRE**

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

**ENVIRONMENTAL PRECAUTIONS**

Do not allow to enter drains, sewers or watercourses.

**SPILL CLEAN UP METHODS**

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Static electricity and formation of sparks must be prevented. Risk of vapour concentration on the floor and in low-lying areas. Provide good ventilation. Avoid inhalation of vapours/spray and contact with skin and eyes.

**STORAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Store in tightly closed original container in a dry, cool and well-ventilated place. Take precautionary measures against static discharges. Avoid contact with oxidising agents.

**STORAGE CLASS**

Flammable liquid storage.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
CALCIUM CARBONATE	WEL		4 mg/m <sup>3</sup>			
CRYSTALLINE QUARTZ	WEL		0,1 mg/m <sup>3</sup>			
MAGNESIUM CARBONATE	WEL		4 mg/m <sup>3</sup>			
PETROLEUM ASPHALT	WEL		5 mg/m <sup>3</sup>		10 mg/m <sup>3</sup>	

WEL = Workplace Exposure Limit.

**PROTECTIVE EQUIPMENT**

**ENERGIZER K PLUS FR****ENGINEERING MEASURES**

Provide adequate ventilation.

**HAND PROTECTION**

Use protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

**EYE PROTECTION**

Wear approved safety goggles.

**HYGIENE MEASURES**

Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke. Wash hands after handling.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Thixotropic liquid.		
COLOUR	Off white.		
ODOUR	Mild		
SOLUBILITY	Insoluble in water		
BOILING POINT (°C)	149°C - 179°C	RELATIVE DENSITY	0.96
VAPOUR DENSITY (air=1)	4.3	VAPOUR PRESSURE	10 mm Hg @ 37.7°C
EVAPORATION RATE	0.1 (ButAc=1)	VOLATILE BY VOL. (%)	20 -24%
FLASH POINT (°C)	38°C TCC (Tag closed cup).		

**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions and recommended use.

**CONDITIONS TO AVOID**

Avoid contact with strong oxidisers. Avoid heat, flames and other sources of ignition.

**HAZARDOUS POLYMERISATION**

Will not polymerise.

**MATERIALS TO AVOID**

Strong oxidising substances.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Hydrocarbons.

**11 TOXICOLOGICAL INFORMATION****INHALATION**

Vapours may cause headache, fatigue, dizziness and nausea.

**INGESTION**

Harmful: may cause lung damage if swallowed. Drowsiness, dizziness, disorientation, vertigo.

**SKIN CONTACT**

Prolonged contact may cause redness, irritation and dry skin.

**EYE CONTACT**

Spray and vapour in the eyes may cause irritation and smarting.

**MEDICAL SYMPTOMS**

Headache. Dizziness. Nausea, vomiting.

**MEDICAL CONSIDERATIONS**

Liver and/or kidney problems. Skin disorders and allergies. Convulsive disorders, CNS problems.

## ENERGIZER K PLUS FR

## 12 ECOLOGICAL INFORMATION

## ECOTOXICITY

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

## 13 DISPOSAL CONSIDERATIONS

## DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Recover and reclaim or recycle, if practical.

## 14 TRANSPORT INFORMATION



UK ROAD CLASS	3		
PROPER SHIPPING NAME	TARS, LIQUID		
UN NO. ROAD	1999	UK ROAD PACK GR.	III
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III	HAZARD No. (ADR)	30
ADR LABEL NO.	3	HAZCHEM CODE	2WE
CEFIC TEC(R) NO.	30GF1-III, 30GF1-sp	RID CLASS NO.	3
RID PACK GROUP	III	UN NO. SEA	1999
IMDG CLASS	3	IMDG PACK GR.	III
EMS	F-E, S-E	MFAG	See Guide
MARINE POLLUTANT	No.	UN NO. AIR	1999
AIR CLASS	3	AIR PACK GR.	III

## 15 REGULATORY INFORMATION

## LABELLING



Harmful

CONTAINS PETROLEUM NAPHTHA, LIGHT AROMATIC

## RISK PHRASES

R10	Flammable.
R65	Harmful: may cause lung damage if swallowed.

## SAFETY PHRASES

S51	Use only in well-ventilated areas.
S60	This material and its container must be disposed of as hazardous waste.
S62	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

## EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

