



## FLASHING BOND

### 5 FIRE-FIGHTING MEASURES

**EXTINGUISHING MEDIA**

Extinguish with foam, carbon dioxide or dry powder. Do not use water jet as an extinguisher, as this will spread the fire.

**SPECIAL FIRE FIGHTING PROCEDURES**

Avoid breathing fire vapours. Containers close to fire should be removed immediately or cooled with water. Keep run-off water out of sewers and water sources. Dike for water control.

**UNUSUAL FIRE & EXPLOSION HAZARDS**

**FLAMMABLE.** Solvent vapours may form explosive mixtures with air. May travel considerable distance to source of ignition and flash back.

**SPECIFIC HAZARDS**

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Hydrocarbons.

**PROTECTIVE MEASURES IN FIRE**

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

### 6 ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

**ENVIRONMENTAL PRECAUTIONS**

Do not allow to enter drains, sewers or watercourses.

**SPILL CLEAN UP METHODS**

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

### 7 HANDLING AND STORAGE

**USAGE PRECAUTIONS**

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Static electricity and formation of sparks must be prevented. Risk of vapour concentration on the floor and in low-lying areas. Provide good ventilation. Avoid inhalation of vapours/spray and contact with skin and eyes.

**STORAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Store in tightly closed original container in a dry, cool and well-ventilated place. Take precautionary measures against static discharges. Avoid contact with oxidising agents.

**STORAGE CLASS**

Flammable liquid storage.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
CRYSTALLINE QUARTZ	WEL		0,1 mg/m <sup>3</sup>			
PETROLEUM ASPHALT	WEL		5 mg/m <sup>3</sup>		10 mg/m <sup>3</sup>	

WEL = Workplace Exposure Limit.

**PROTECTIVE EQUIPMENT**



**ENGINEERING MEASURES**

Provide adequate ventilation.

**FLASHING BOND****RESPIRATORY EQUIPMENT**

If ventilation is insufficient, suitable respiratory protection must be provided.

**HAND PROTECTION**

Use protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

**EYE PROTECTION**

Wear approved safety goggles.

**HYGIENE MEASURES**

Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke. Wash hands after handling.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Liquid		
COLOUR	Black		
ODOUR	Hydrocarbon		
SOLUBILITY	Insoluble in water		
BOILING POINT (°C)	149°C - 199°C	RELATIVE DENSITY	1.03
VAPOUR PRESSURE	6 mm Hg @ 37.7°C	VOLATILE BY VOL. (%)	21 -25%
FLASH POINT (°C)	41°C TCC (Tag closed cup).	AUTO IGNITION TEMPERATURE (°C)	282°C
VOLATILE ORGANIC COMPOUND (VOC)	250 g/litre		

**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions and recommended use.

**CONDITIONS TO AVOID**

Avoid heat, flames and other sources of ignition.

**HAZARDOUS POLYMERISATION**

Will not polymerise.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Hydrocarbons.

**11 TOXICOLOGICAL INFORMATION****INHALATION**

Vapours may cause headache, fatigue, dizziness and nausea.

**INGESTION**

Harmful: may cause lung damage if swallowed. Drowsiness, dizziness, disorientation, vertigo.

**SKIN CONTACT**

Prolonged contact may cause redness, irritation and dry skin.

**EYE CONTACT**

Spray and vapour in the eyes may cause irritation and smarting.

Name	PETROLEUM ASPHALT
Toxic Dose 1 - LD 50	5,000 mg/kg (oral rat)

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Name	PETROLEUM ASPHALT
EC 50, 48 Hrs, DAPHNIA, mg/l	6.14

## FLASHING BOND

## 13 DISPOSAL CONSIDERATIONS

## DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Recover and reclaim or recycle, if practical.

## 14 TRANSPORT INFORMATION



UK ROAD CLASS	3		
PROPER SHIPPING NAME	TARS, LIQUID		
UN NO. ROAD	1999	UK ROAD PACK GR.	III
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III	HAZARD No. (ADR)	30
ADR LABEL NO.	3	HAZCHEM CODE	2WE
CEFIC TEC(R) NO.	30GF1-III, 30GF1-sp	RID CLASS NO.	3
RID PACK GROUP	III	UN NO. SEA	1999
IMDG CLASS	3	IMDG PACK GR.	III
EMS	F-E, S-E	MFAG	See Guide
MARINE POLLUTANT	No.	UN NO. AIR	1999
AIR CLASS	3	AIR PACK GR.	III

## 15 REGULATORY INFORMATION

## LABELLING



Harmful

## CONTAINS

STODDARD SOLVENT

## RISK PHRASES

R10	Flammable.
R65	Harmful: may cause lung damage if swallowed.

## SAFETY PHRASES

S51	Use only in well-ventilated areas.
S60	This material and its container must be disposed of as hazardous waste.
S62	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

## EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

## STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

## APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

## GUIDANCE NOTES

Workplace Exposure Limits EH40.

FLASHING BOND

**16 OTHER INFORMATION**

REVISION DATE 07-2008

RISK PHRASES IN FULL

- R10 Flammable.
- R65 Harmful: may cause lung damage if swallowed.
- NC Not classified.