



SAFETY DATA SHEET METAL WHITE 2 ELASTOMERIC BASE COATING

According to Regulation (EC) No 1907/2006

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	METAL WHITE 2 ELASTOMERIC BASE COATING
PRODUCT NO.	5307
APPLICATION	Paint
SUPPLIER	Garland Company UK Ltd, Unit 5, Glevum Works, Upton Street, Gloucester GL1 4LA UK Tel: 01452 330 646 Fax: 01452 330 657 email: info@garlandukltd.co.uk
EMERGENCY TELEPHONE	01452 330646 09:00 - 17:00 Monday to Friday

2 HAZARDS IDENTIFICATION

Flammable. Harmful: may cause lung damage if swallowed.

CLASSIFICATION Xn;R65. R10.

PHYSICAL AND CHEMICAL HAZARDS

Flammable. Vapours are heavier than air and may travel along the floor and in the bottom of containers.

HUMAN HEALTH

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
STODDARD SOLVENT	232-489-3	8052-41-3	30-70%	Xn;R65. R10.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Vapours may cause drowsiness and dizziness. Move the exposed person to fresh air at once. Get medical attention if any discomfort continues. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.

INGESTION

Harmful: may cause lung damage if swallowed. Rinse mouth thoroughly. Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Get medical attention immediately!

SKIN CONTACT

Prolonged skin contact may cause redness, irritation and dry skin. Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Splashes may irritate. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

METAL WHITE 2 ELASTOMERIC BASE COATING

EXTINGUISHING MEDIA

Extinguish with foam, carbon dioxide or dry powder. Do not use water jet as an extinguisher, as this will spread the fire.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Containers close to fire should be removed immediately or cooled with water. Keep run-off water out of sewers and water sources. Dike for water control.

UNUSUAL FIRE & EXPLOSION HAZARDS

FLAMMABLE. Solvent vapours may form explosive mixtures with air. May travel considerable distance to source of ignition and flash back.

SPECIFIC HAZARDS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrocarbons.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses.

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Static electricity and formation of sparks must be prevented. Risk of vapour concentration on the floor and in low-lying areas. Provide good ventilation. Avoid inhalation of vapours/spray and contact with skin and eyes.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Store in tightly closed original container in a dry, cool and well-ventilated place. Take precautionary measures against static discharges. Avoid contact with oxidising agents.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate ventilation.

RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided.

HAND PROTECTION

Use protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear approved safety goggles.

HYGIENE MEASURES

Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke. Wash hands after handling.

METAL WHITE 2 ELASTOMERIC BASE COATING**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Thixotropic liquid.		
COLOUR	Off white.		
ODOUR	Mild		
SOLUBILITY	Insoluble in water		
BOILING POINT (°C)	151.6°C - 198.9°C (liquid)	RELATIVE DENSITY	1.05
VAPOUR DENSITY (air=1)	4.8 (solvent)	VAPOUR PRESSURE	< 10 mm Hg not noted
FLASH POINT (°C)	37.8°C CC (Closed cup).	FLAMMABILITY LIMIT - LOWER(%)	0.7%
FLAMMABILITY LIMIT - UPPER(%)	6.0%		

10 STABILITY AND REACTIVITY**STABILITY**

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

HAZARDOUS POLYMERISATION

Will not polymerise.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrocarbons.

11 TOXICOLOGICAL INFORMATION**INHALATION**

Vapours may cause headache, fatigue, dizziness and nausea.

INGESTION

Harmful: may cause lung damage if swallowed. Drowsiness, dizziness, disorientation, vertigo.

SKIN CONTACT

Prolonged contact may cause redness, irritation and dry skin.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

13 DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements. Recover and reclaim or recycle, if practical.

14 TRANSPORT INFORMATION

METAL WHITE 2 ELASTOMERIC BASE COATING

UK ROAD CLASS	3	UK ROAD PACK GR.	III
PROPER SHIPPING NAME	PAINT	ADR CLASS	Class 3: Flammable liquids.
UN NO. ROAD	1263	TUNNEL RESTRICTION CODE	(D/E)
ADR CLASS NO.	3	ADR LABEL NO.	3
ADR PACK GROUP	III	CEFIC TEC(R) NO.	30GF1-III, 30GF1-sp
HAZARD No. (ADR)	30	RID PACK GROUP	III
HAZCHEM CODE	•3YE	IMDG CLASS	3
RID CLASS NO.	3	EMS	F-E, S-E
UN NO. SEA	1263	AIR CLASS	3
IMDG PACK GR.	III		
UN NO. AIR	1263		
AIR PACK GR.	III		

15 REGULATORY INFORMATION

LABELLING



Harmful

CONTAINS STODDARD SOLVENT

RISK PHRASES

- R10 Flammable.
- R65 Harmful: may cause lung damage if swallowed.

SAFETY PHRASES

- S51 Use only in well-ventilated areas.
- S60 This material and its container must be disposed of as hazardous waste.
- S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

REVISION COMMENTS

This is first issue.

REVISION DATE 04-2010

RISK PHRASES IN FULL

- R10 Flammable.
- R65 Harmful: may cause lung damage if swallowed.