



## SAFETY DATA SHEET GMX ELASTOMERIC H20

According to Regulation (EC) No 1907/2006

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME                    GMX ELASTOMERIC H20  
 PRODUCT NO.                    5-903  
 APPLICATION                    Waterproofing membrane.  
 SUPPLIER                        Garland Company UK Ltd,  
    Unit 5, Glevum Works,  
    Upton Street,  
    Gloucester GL1 4LA  
    UK  
    Tel: 01452 330 646  
    Fax: 01452 330 657  
    email: info@garlandukltd.co.uk  
 EMERGENCY TELEPHONE        01452 330646  
    09:00 - 17:00 Monday to Friday

### 2 HAZARDS IDENTIFICATION

Flammable. Harmful by inhalation. Harmful: may cause lung damage if swallowed. May cause sensitisation by inhalation.

CLASSIFICATION                    Xn;R20, R65. R42. R10.

#### PHYSICAL AND CHEMICAL HAZARDS

Flammable. Vapours are heavier than air and may travel along the floor and in the bottom of containers.

#### HUMAN HEALTH

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Harmful by inhalation. Preparation contains small volumes of isocyanate which may cause allergic reaction and irritation of respiratory system. See section 11 for additional information on health hazards.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
PETROLEUM NAPHTHA, LIGHT AROMATIC	265-199-0	64742-95-6	1-3%	Xn;R65. R10.
STODDARD SOLVENT	232-489-3	8052-41-3	10-15%	Xn;R65. R10.
TOLUENE-DIISOCYANATE	247-722-4	26471-62-5	< 0.14%	Carc. Cat. 3;R40 T+;R26 R42/43 Xi;R36/37/38 R52/53

The Full Text for all R-Phrases are Displayed in Section 16

### 4 FIRST-AID MEASURES

#### INHALATION

By frequent inhalation of vapours, respiratory allergy may develop. Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

#### INGESTION

May cause discomfort if swallowed. Rinse mouth thoroughly. Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Get medical attention immediately!

#### SKIN CONTACT

Prolonged skin contact may cause redness, irritation and dry skin. May cause allergic skin disorders in sensitive individuals. Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.

## GMX ELASTOMERIC H20

### EYE CONTACT

Splashes may irritate. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

## 5 FIRE-FIGHTING MEASURES

### EXTINGUISHING MEDIA

Extinguish with foam, carbon dioxide or dry powder. Do not use water jet as an extinguisher, as this will spread the fire.

### SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Containers close to fire should be removed immediately or cooled with water. Keep run-off water out of sewers and water sources. Dike for water control.

### SPECIFIC HAZARDS

By fire, toxic gases may be formed (COx, NOx). Hydrogen cyanide (HCN).

### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

### ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses.

### SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Provide good ventilation. Avoid inhalation of vapours/spray and contact with skin and eyes. Persons susceptible for allergic reactions should not handle this product. Persons with impaired lung functions should not handle this preparation.

### STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Store in tightly closed original container in a dry, cool and well-ventilated place. Avoid contact with oxidising agents.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### PROTECTIVE EQUIPMENT



### ENGINEERING MEASURES

Provide adequate ventilation.

### RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided.

### HAND PROTECTION

Use protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

### EYE PROTECTION

Wear approved safety goggles.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

## GMX ELASTOMERIC H20

### HYGIENE MEASURES

Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke. Wash hands after handling.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Black		
ODOUR	Aromatic.		
SOLUBILITY	Reacts slowly with water.		
BOILING POINT (°C)	149°C - 288°C	RELATIVE DENSITY	1.09 - 1.20
VAPOUR DENSITY (air=1)	> 1	EVAPORATION RATE	< 1.0 (ButAc=1)
FLASH POINT (°C)	48.9°C	FLAMMABILITY LIMIT - UPPER(%)	6.0%
VOLATILE ORGANIC COMPOUND (VOC)	< 140 g/litre		

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions and recommended use.

### CONDITIONS TO AVOID

Avoid contact with strong oxidisers. Avoid heat, flames and other sources of ignition.

### MATERIALS TO AVOID

Strong oxidising substances. Alcohols. Amines. Ammonia Bases. Water.

### HAZARDOUS DECOMPOSITION PRODUCTS

By fire, toxic gases (CO, CO<sub>2</sub>, NO<sub>x</sub>) may be formed. Hydrogen cyanide (HCN).

## 11 TOXICOLOGICAL INFORMATION

### INHALATION

Harmful by inhalation. May cause sensitisation by inhalation.

### INGESTION

Harmful: may cause lung damage if swallowed.

### SKIN CONTACT

Liquid may irritate the skin.

### EYE CONTACT

May irritate eyes.

### MEDICAL CONSIDERATIONS

Allergies. Chronic respiratory and obstructive airway diseases.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

Avoid discharge to the aquatic environment.

## 13 DISPOSAL CONSIDERATIONS

### DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Recover and reclaim or recycle, if practical.

## 14 TRANSPORT INFORMATION

## GMX ELASTOMERIC H20



UK ROAD CLASS	3		
PROPER SHIPPING NAME	PAINT		
UN NO. ROAD	1263	UK ROAD PACK GR.	III
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III	TUNNEL RESTRICTION CODE	(D/E)
HAZARD No. (ADR)	30	ADR LABEL NO.	3
HAZCHEM CODE	•3YE	CEFIC TEC(R) NO.	30GF1-III, 30GF1-sp
RID CLASS NO.	3	RID PACK GROUP	III
UN NO. SEA	1263	IMDG CLASS	3
IMDG PACK GR.	III	EMS	F-E, S-E
UN NO. AIR	1263	AIR CLASS	3
AIR PACK GR.	III		

## 15 REGULATORY INFORMATION

### LABELLING



Harmful

CONTAINS STODDARD SOLVENT  
TOLUENE-DIISOCYANATE

### RISK PHRASES

R10 Flammable.  
R20 Harmful by inhalation.  
R42 May cause sensitisation by inhalation.  
R65 Harmful: may cause lung damage if swallowed.

### SAFETY PHRASES

S23 Do not breathe vapour/spray.  
S38 In case of insufficient ventilation, wear suitable respiratory equipment.  
S45 In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).  
S60 This material and its container must be disposed of as hazardous waste.  
P4 Contains isocyanates. See information supplied by the manufacturer.

### EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

### STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

### APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

### GUIDANCE NOTES

Workplace Exposure Limits EH40.

## 16 OTHER INFORMATION

## GMX ELASTOMERIC H20

### REVISION COMMENTS

This is first issue.

REVISION DATE                      05-2010

### RISK PHRASES IN FULL

R10	Flammable.
R26	Very toxic by inhalation.
R36/37/38	Irritating to eyes, respiratory system and skin.
R40	Limited evidence of a carcinogenic effect.
R42/43	May cause sensitisation by inhalation and skin contact.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.